

County Surveyor's Record, Douglas County, Oregon

15426

Retracement of a Portion of the East Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

Beginning at the cor. of secs. 25 and 36 only, on the E. bdy. of T. 19 S. R. 10 W., occupied by the original corner tree, a fir, 28 ins. diam., mkd. T19S S36 on SW., R10W S25 on NW., 1 groove on S., and 5 grooves on N. sides, from which the original bearing trees:

A fir, 34 ins. diam., bears S. 83° W., 71 lks. dist., with healed blaze.

A fir, 34 ins. diam., bears N. 3 1/2° W., 6 lks. dist., with healed blaze.

N. 4° 28' E., along E. bdy. of sec. 25.

Descend 90 ft. over NE. slope, through heavy timber and dense undergrowth.

10.77

The closing cor. of secs. 30 and 31, T. 19 S., R. 9 W., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap mkd.

T 19 S T 19 S
S 25 S 30
S 31 CC

R 10 W R 9 W
1958

from which bears trees mkd. by Tillman, Holm, and Brooks, in 1958

A hemlock, 18 ins. diam., bears N. 24 1/2° E., 57 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A hemlock, 45 ins. diam., bears S. 9° E., 34 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

N. 4° 16' E., beginning new measurement.

Descend 30 ft. over NE slope.

2.20

North Fork Smith River, 70 lks. wide, course S. 65° E.; asc. 90 ft. over SW. slope.

18.55

Top of ascent, slopes W.; desc. 85 ft. over NW. slope.

32.60

North Fork Smith River, 25 lks. wide, course W.; asc. 60 ft. over SE. slope.

35.72

The 1/4 sec. cor. of sec. 25 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4
T 19 S
S 25
R 10 W
1958

from which bearing trees mkd. by Tillman, Holm, and Brooks, in 1958

A fir, 23 ins. diam., bears S. 11° W., 16 lks. dist., mkd. 1/4 S25 BT.