

County Surveyor's Record, Douglas County, Oregon

15427

Retracement of a Portion of the East Boundary
T 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

A cedar, 15 ins. diam., bears N. 34 1/2° W., 28 lks.
dist., mkd 1/4 S 25 BT.

N. 2° 59' E., beginning new measurement.

Ascend 155 ft. over SE. slope.

6.50 Spur, slopes S. 65° E.; desc. 105 ft. over NE. slope.

10.77 The 1/4 sec. cor. of sec. 30 only, T. 19 S., R. 9 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4
T 19 S
S 30
R 9 W

1958

from which bearing trees mkd. by Tillman, Holm, and Brooks, in 1958

An alder, 21 ins. diam., bears N. 7° E., 55 lks.
dist., mkd. 1/4 S30 BT.

An alder, 26 ins. diam., bears S. 78° E., 43 lks.
dist., mkd. 1/4 S30 BT.

N. 4° 48' E., beginning new measurement.

Descend 15 ft. over NE. slope.

1.75 Creek, 2 lks. wide, course E.; desc. 55 ft. over NE. slope.

16.40 North Fork Smith River, 30 lks. wide, course E.; asc. 285 ft. over SW. slope.

25.70 Spur, slopes N. 80° W.; desc. 60 ft. over NW. slope.

27.40 Ravine, drains W.; asc. 195 ft. over SW. slope.

32.20 Spur, slopes N. 75° W.; desc. 135 ft. over NW. slope.

35.52 The cor. of secs. 24 and 25 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 19 S T 19 S
S 24 S 30
S 25
R 10 W R 9 W

1958

from which bearing trees mkd. by Tillman, Holm, and Brooks, in 1958

A cedar, 60 ins. diam., bears S. 25° W., 47 lks.
dist., mkd. T19S R10W S25 BT.

A cedar, 33 ins. diam., bears N. 40° W., 68 lks.
dist., mkd. T19S R10W S24 BT.

Corner is located in small ravine, drains W.