

County Surveyor's Record, Douglas County, Oregon

15428

Retracement of a Portion of the East Boundary
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

N. 4° 56' E., along the E. bdy. of sec. 24.

Ascend 85 ft. over SW. slope, through heavy timber and dense undergrowth.

2.15 Spur, slopes W.; desc. 75 ft. over NW. slope.

4.90 Ravine, drains S. 65° W.; asc. 235 ft. over SW. slope.

10.15 Spur, slopes S. 75° W.; desc. 20 ft. over NW. slope.

10.68 The closing cor. of secs. 19 and 30, T. 19 S., R. 9 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 19 S T 19 S
S 24 S 19 C
S 30 C
R 10 W R 9 W
1958

from which bearing trees mkd. by Tillman, Holm, and Brooks, in 1958

A fir, 39 ins. diam., bears N. 45° E., 98 lks. dist., mkd. T19S R9W S19 CC BT.

A fir, 13 ins. diam., bears S. 55° E., 71 lks. dist., mkd. T19S R9W S30 CC BT.

N. 4° 37' E., beginning new measurement.

Descend 60 ft. over NW. slope.

1.45 Ravine, drains W.; asc. 80 ft. over SW. slope.

5.10 Spur, slopes W.; desc. 160 ft. over NW. slope.

9.90 Ravine, drains N. 60° W.; asc. 5 ft. over SW. slope.

13.50 Top of ascent, slopes W.; desc. 245 ft. over NW. slope.

19.60 Creek, 2 lks. wide, course N. 85° W ; asc. 200 ft. over SW. slope.

24.10 Spur, slopes S. 80° W.; desc. 305 ft. over NW. slope.

30.70 Ravine, drains NW.; desc. 1 ft. over nearly level land.

35.94 The 1/4 sec. cor. of sec. 24 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4
T 19 S
S 24
R 10 W
1958

from which bearing trees mkd. by Tillman, Holm, and Brooks, in 1958

An alder, 25 ins. diam., bears S. 7 1/2° W., 105 lks. dist., mkd. 1/4 S24 BT.