

County Surveyor's Record, Douglas County, Oregon

15430

Retracement of a Portion of the East Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS
9.90

Top of ascent, slopes E.; desc. 30 ft. over NE. slope.

13.20

Creek, 2 lks. wide, course SE.; asc. 80 ft. over SE. slope.

21.30

Top of ascent, slopes E.; desc. 25 ft. over NE. slope.

22.40

Creek, 2 lks. wide, course S. 80° E.; asc. 10 ft. over SE. slope.

22.91

The cor. of secs. 13 and 24 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 19 S T 19 S
S 13
S 24 S 19
R 10 W R 9 W
1958

from which bearing trees mkd. by Tillman, Holm, and Brooks, in 1958

A fir, 45 ins. diam., bears S. 38° W., 124 lks. dist., mkd. T19 R10W S24 BT.

A fir, 40 ins. diam., bears N. 55° W., 70 lks. dist., mkd. T19S R10W S13 BT.

N. 3° 49' E., along the E. bdy. of sec. 13.

Ascend 260 ft. over SE. slope, through heavy timber and dense undergrowth.

2.50

Abandoned dirt road, 15 lks. wide, bears N. 75° W. and S. 75° E.

10.94

The closing cor. of secs. 18 and 19, T. 19 S., R. 9 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 19 S T 19 S
S 13 S 18
S 19 CC
R 10 W R 9 W
1958

*FND OK
R. WARD 6/19/91
M 113-37 A/B*

from which the remains of the bearing trees mkd. by Tillman, Holm, and Brooks, in 1958

A root hole, bears N. 82° E., 63 lks. dist., with a down fir alongside, 60 ins. diam., with healed blaze.

A sawed fir stump, 44 ins. diam., bears S. 6° E., 62 lks. dist., with scribe marks BT visible on open blaze.

and a bearing tree of no record

A fir, 47 ins. diam., bears N. 14° E., 60 lks. dist., with healed blaze.

and a new bearing tree

A cedar, 14 ins. diam., bears S. 28° E., 141 lks. dist., mkd. T19S R9W S19 CC BT.