

# County Surveyor's Record, Douglas County, Oregon

**15431**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the survey executed by Henry L. Chandler,  
Deputy Surveyor, in 1899,  
and the dependent resurvey by Thomas A. Tillman,  
Robert L. Holm, and Floyd A. Brooks,  
Cadastral Surveyors, in 1957-58)

Beginning at the cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 19 S R 9 W				
<table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> </table>	S 26	S 25	S 35	S 36
S 26	S 25			
S 35	S 36			
1958				

from which bearing trees mkd. in 1958

A root hole, bears N. 74° E., 39 lks. dist., with a down fir alongside, 42 ins. diam., with healed blaze.

A root hole, bears S. 47° E., 3 lks. dist., with a down alder alongside, 20 ins. diam., with scribe marks T19S R9W S36 BT visible on bark.

A hemlock snag, 18 ins. diam., bears S. 18° W., 81 lks. dist., with scribe marks T19S R9W S35 BT visible on open blaze.

A root hole, bears N. 60° W., 36 lks. dist., with a down fir alongside, 40 ins. diam., with partially healed blaze.

and new bearing trees

A hemlock, 38 ins. diam., bears N. 32 1/4° E., 65 lks. dist., mkd. T19S R9W S25 BT.

A fir, 37 ins. diam., bears S. 36 3/4° W., 130 lks. dist., mkd. T19S R9W S35 BT.

A fir, 36 ins. diam., bears N. 32 1/2° W., 100 lks. dist., mkd. T19S R9W S26 BT.

No other suitable trees available within limits.

N. 2° 17' W., bet. secs. 25 and 26, marking and blazing the true line.

Ascend 235 ft. over SW. slope, through heavy timber and dense undergrowth.

35.90

Spur, slopes W.; desc. 45 ft. over NW. slope.

38.15

Creek, 1 lk. wide, course N. 80° W.; asc. 80 ft. over SW. slope.

40.67

Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.