

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

15432

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T 19 S R 9 W
1/4
S 26 | S 25
1968

from which

An alder, 15 ins. diam., bears N. 34 1/2° E., 12 lks. dist., mkd. 1/4 S25 BT.

A maple, 10 ins. diam., bears S. 26 1/2° W., 25 lks. dist., mkd 1/4 S26 BT.

Ascend 395 ft. over SW. slope.

54.80

Paved road, 30 lks. wide, bears N. 30° W. and S. 30° E.

61.005

Point for the N 1/16 sec. cor. of secs. 25 and 26.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

N 1/16
S 26 | S 25
1968

from which

A fir, 32 ins. diam., bears S. 77° E., 37 lks. dist., mkd. N 1/16 S25 BT.

A fir, 34 ins. diam., bears N. 62° W., 71 lks. dist., mkd. N 1/16 S26 BT.

Ascend 35 ft. over SW. slope.

62.75

Ridge, bears N. 60° W. and S. 60° E.; desc. 45 ft. over N. slope.

64.45

Bottom of descent, slopes N. 70° E.; asc. 25 ft. over SE. slope.

66.60

Spur, slopes N. 70° E.; desc. 145 ft. over N. slope.

72.80

Ravine, drains S. 60° E.; asc. 275 ft. over SW. slope, changing to S. slope.

77.55

Dirt road, 20 lks. wide, bears E. and W.

78.70

Ridge, bears E. and W.; desc. 90 ft. over NE. slope.

81.34

Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 19 S R 9 W
S 23 | S 24
S 26 | S 25
1968

from which