

County Surveyor's Record, Douglas County, Oregon

15433

Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S. R. 9 W., Willamette Meridian, Oregon

CHAINS

A hemlock, 8 ins. diam., bears N. 60° E., 34 lks. dist., mkd. T19S R9W S24 BT.

A fir, 27 ins. diam., bears S. 54 1/2° E., 35 lks. dist., mkd. T19S R9W S25 BT.

A hemlock, 13 ins. diam., bears S. 77° W., 54 lks. dist., mkd. T19S R9W S26 BT.

A fir, 26 ins. diam., bears N. 50 1/2° W., 55 lks. dist., mkd. T19S R9W S23 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock cedar, alder, maple, madrone, and yew; undergrowth, vine maple, huckleberry, salmonberry, rhododendron, hazel, and fern.

S. 88° 55' E., bet. secs. 24 and 25.

Descend 165 ft. over NE. slope, through heavy timber and dense undergrowth.

3.65 Ravine, drains N. 20° E.; asc. 35 ft. over NW. slope.

7.70 Spur, slopes N. 50° E.; desc. 275 ft. over SE. slope.

13.20 Ravine, drains N. 60° E.; asc. 90 ft. over NW. slope.

18.40 Spur, slopes N.; desc. 305 ft. over NE. slope.

25.60 Ravine, drains N. 40° E.; desc. 25 ft. over NE. slope.

27.80 Creek, 2 lks. wide, course S. 70° E.; asc. 55 ft. over SW slope.

36.20 Spur, slopes S.; desc. 45 ft. over SE slope.

38.90 Ravine, drains S.; asc. 60 ft. over SW. slope.

40.61 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T 19 S R 9 W

1/4 $\frac{S\ 24}{S\ 25}$

1968

from which

A fir, 36 ins. diam., bears N. 2° E., 17 lks. dist., mkd. 1/4 S24 BT.

A fir, 42 ins. diam., bears S. 30° E., 9 lks. dist., mkd. 1/4 S25 BT.

Ascend 310 ft. over SW. slope.

60. 915 Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.