

County Surveyor's Record, Douglas County, Oregon

15434

Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

E 1/16 $\frac{S\ 24}{S\ 25}$
1968

from which

A fir, 25 ins. diam., bears N. 12° E., 47 lks.
dist., mkd. E 1/16 S24 BT.

A fir, 30 ins. diam., bears S. 38° E., 77 lks.
dist., mkd. E 1/16 S25 BT.

Ascend 110 ft. over broken SW. slope.

- 71.30 Spur ridge, bears N. 60° W. and S. 60° E.; asc. 50 ft. along N. slope.
- 75.90 Spur, slopes NW.; desc. 85 ft. over NE. slope.
- 78.30 Ravine, drains N.; asc. 50 ft. over NW. slope.
- 80.80 Spur, slopes N.; desc. 115 ft. over NE. slope.
- 83.60 Ravine, drains N.; asc. 210 ft. over NW. slope.
- 93.60 Spur, slopes N.; desc. 250 ft. over NE. slope.
- 101.63 The closing cor. of secs. 24 and 25, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 19 S T 19 S
CC $\frac{S\ 24}{S\ 25}$ | R 8 W
 | S 19
 R 9 W
 1957

from which bearing trees mkd. in 1957

An alder snag, 16 ins. diam., bears S. 33 1/2 ° W., 17 lks. dist., mkd. T19S R9W S25 CC BT.

An alder snag, 10 ins. diam., bears N. 76 1/2° W., 57 lks. dist., mkd. T19S R9W S24 CC BT.

and new bearing trees

An alder, 18 ins. diam., bears S. 33° W., 53 lks. dist., mkd. T19S R9W S25 CC BT.

A maple, 15 ins. diam., bears N. 87 1/4° W., 105 lks. dist., mkd. T19S R9W S24 CC BT.

From this point, the 1/4 sec. cor. of sec. 19 only, bears N. 0° 25' W., 2.23 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 19 S
1/4 S 19
R 8 W
1957

from which the bearing trees mkd. in 1957