

County Surveyor's Record, Douglas County, Oregon

15437

Dependent Resurvey, Portion of Subdivisional Lines,
T 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
0.50	Beaver Creek, 17 lks. wide, course SE.; asc. 380 ft. over SW. slope.
21.95	Spur, slopes N. 60° W.; desc. 140 ft. over N. slope. changing to NW. slope.
32.20	Creek, 2 lks. wide, course S. 30° W.; asc. 450 ft. over S. slope.
41.20	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 19 S R 9 W 1/4 S 27 S 26 1968
	from which
	A fir, 20 ins. diam., bears S. 73° E., 23 lks. dist., mkd. 1/4 S26 BT.
	A fir, 25 ins. diam., bears N. 17° W., 6 lks. dist., mkd. 1/4 S27 BT.
	Corner is located on ridge, bears N. 60° W. and S. 60° E.
	Descend 80 ft. over N. slope.
43.50	Gravelled road, 30 lks. wide, bears N. 60° W. and S. 60° E.
44.00	Ravine, drains N. 70° E.; asc. 80 ft. over SE. slope.
47.10	Spur, slopes E.; desc. 220 ft. over N. slope.
51.40	Creek, 2 lks. wide, course N. 80° E.; asc. 350 ft. over S. slope.
58.70	Spur, slopes E.; desc. 110 ft. over NE. slope.
61.80	Point for the N 1/16 sec. cor. of secs. 26 and 27. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 27 S 26 1968
	from which
	A fir, 20 ins. diam., bears N. 43 1/2° E., 89 lks. dist., mkd. N 1/16 S26 BT.
	An alder, 18 ins. diam., bears N. 60° W., 54 lks. dist., mkd. N 1/16 S27 BT.
	Descend 280 ft. over NE. slope.
71.50	Creek, 3 lks. wide, course S. 70° E.; desc. 35 ft. along E. slope.