

County Surveyor's Record, Douglas County, Oregon

15439 Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 52 1/2° E., 43 1/2 lks. dist., mkd. 1/4 S23 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 65° E., 47 lks. dist., mkd. 1/4 S26 BT.</p> <p>Descend 50 ft. over NW. slope.</p>
43.45	Creek, 1 lk. wide, course S.; asc. 285 ft. over SE. slope, changing to broken E. slope.
57.35	Spur, slopes S. 10° E.; desc. 310 ft. over W. slope.
61.05	Point for the W 1/16 sec. cor. of secs. 23 and 26.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 23}{S\ 26}$</p> <p style="text-align: center;">1976</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 9° E., 38 1/2 lks. dist., mkd. W 1/16 S23 BT.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 7° E., 32 lks. dist., mkd. W 1/16 S26 BT.</p> <p>Descend 260 ft. over W. slope.</p>
71.25	Ravine, drains S. 50° W.; desc. 70 ft. over SW. slope.
75.80	Gold Creek, 3 lks. wide, course S. 20° E.; asc. 120 ft. over NE. slope.
81.40	The cor. of secs. 22, 23, 26, and 27.
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, chinquapin, maple, alder, dogwood, and yew; undergrowth, vine maple, rhododendron, huckleberry, salmonberry, hazel, salal, and fern.</p>
	<p>N. 1° 06' E., bet. secs. 22 and 23.</p> <p>Descend 100 ft. over NE. slope.</p>
3.60	Ravine, drains E.; asc. 180 ft. along E. slope.
17.70	Ravine, drains S. 70° E.; asc. 150 ft. over SE. slope.
25.70	Spur, slopes E.; desc. 50 ft. over NE. slope.
33.90	Ravine, drains SE.; asc. 200 ft. over SE. slope.
41.13	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 9 W 1/4 S 22 S 23 1968</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 49° E., 22 lks. dist., mkd. 1/4 S23 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 81° W., 9 lks. dist., mkd. 1/4 S22 BT.</p> <p>Ascend 20 ft. over SE. slope.</p>
42.15	Spur, slopes SE.; desc. 70 ft. over NE. slope.