

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **15440**
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

49.35 Ravine, drains SE.; asc. 900 ft. over SE. slope, changing to S. slope.

79.70 Ridge, bears E. and W.; desc. 40 ft. over N. slope; also gravelled road, 30 lks. wide, bears NE. and NW., in curve

82.26 The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above ground, with brass cap mkd.

T 19 S R 9 W
S 15 | S 14
S 22 | S 23
1958

from which bearing trees mkd. in 1958

A cedar, 9 ins. diam., bears N. 47° E., 74 lks. dist., mkd. T19S R9W S14 BT

A cedar, 10 ins. diam., bears S. 46° E., 42 1/2 lks. dist., mkd. T19S R9W S23 BT.

A fir, 25 ins. diam., bears S. 61° W., 70 lks. dist., mkd. T19S R9W S22 BT

A fir, 37 ins. diam., bears N. 35° W., 66 lks. dist., mkd. T19S R9W S15 BT.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, cedar, chinquapin, alder, maple, madrone, dogwood, and yew; undergrowth, vine maple, salal, huckleberry, salmonberry, hazel, rhododendron, and fern.

From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., remonumented and recorded by Vernon Tracy, Deputy County Surveyor, in 1969, at the exact position of the iron post set by Mensch, in 1922, with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 19 S R 9 W
S 33 | S 34
S 4
T 20 S
1969

from which the remains of a bearing tree mkd. by Mensch, in 1922

A fir snag, 30 ins. diam., bears N. 70° W., 36 lks. dist., with healed blaze. (Record, N. 31° W.)

and a bearing tree mkd. by Tracy

A maple, 8 ins. diam., bears N. 52° W., 48 lks. dist., with scribe marks T19S R9W S33 CS BT visible on open blaze.

N. 1° 27' E., bet. secs. 33 and 34.

Ascend 30 ft. over SW. slope, through heavy timber and dense undergrowth.

0.75 Spur, slopes S. 70° W.; desc. 60 ft. over NW. slope.