

# County Surveyor's Record, Douglas County, Oregon

15443

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS																					
	<p>N. 1° 31' W., bet. secs. 27 and 28.</p> <p>Ascend 205 ft. over S. slope, through heavy timber and dense undergrowth.</p>																				
3.90	<p>Spur, slopes S. 80° E.; desc. 130 ft. over NE. slope.</p>																				
9.10	<p>Ravine, drains S. 80° E.; asc. 185 ft. over SE. slope.</p>																				
15.50	<p>Spur, slopes S. 70° E.; desc. 175 ft. over NE slope.</p>																				
19.40	<p>Ravine, drains S. 70° E.; asc. 320 ft. over SE. slope.</p>																				
28.80	<p>Ridge, bears E. and W.; desc. 255 ft. over N. slope.</p>																				
40.98	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td></td><td style="text-align: center;">1/4</td><td></td></tr> <tr><td style="text-align: center;">S 28</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 27</td></tr> <tr><td style="text-align: center;">T 19 S</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 9 W</td></tr> <tr><td></td><td style="text-align: center;">1969</td><td></td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 29 1/2° E., 25 lks. dist., mkd. 1/4 S27 BT.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears S. 61° W., 67 lks. dist., mkd. 1/4 S28 BT.</p> <p>Descend 175 ft. over broken NW. slope.</p>		1/4		S 28		S 27	T 19 S		R 9 W		1969									
	1/4																				
S 28		S 27																			
T 19 S		R 9 W																			
	1969																				
47.70	<p>Creek, 3 lks. wide, course S. 50° W.; asc. 430 ft. over SE. slope.</p>																				
81.96	<p>Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td></td><td style="text-align: center;">T 19 S</td><td style="text-align: center;">R 9 W</td><td></td></tr> <tr><td></td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td></td></tr> <tr><td></td><td style="border-left: 1px solid black; text-align: center;">S 21</td><td style="border-left: 1px solid black; text-align: center;">S 22</td><td></td></tr> <tr><td></td><td style="border-left: 1px solid black; text-align: center;">S 28</td><td style="border-left: 1px solid black; text-align: center;">S 27</td><td></td></tr> <tr><td></td><td></td><td style="text-align: center;">1968</td><td></td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">An alder, 20 ins. diam., bears N. 61 1/2° E., 46 lks. dist., mkd. T19S R9W S22 BT.</p> <p style="padding-left: 40px;">An alder, 22 ins. diam., bears S. 69° E., 23 lks. dist., mkd. T19S R9W S27 BT.</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears S. 48° W., 185 lks. dist., mkd. T19S R9W S28 BT.</p> <p style="padding-left: 40px;">An alder, 18 ins. diam., bears N. 82° W., 210 lks. dist., mkd. T19S R9W S21 BT.</p>		T 19 S	R 9 W							S 21	S 22			S 28	S 27				1968	
	T 19 S	R 9 W																			
	S 21	S 22																			
	S 28	S 27																			
		1968																			