

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion fo Subdivisional Lines,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

15446

CHAINS

T 19 S R 9 W
S 16 | S 15
S 21 | S 22
1968

from which

A fir, 28 ins. diam., bears N. 57° E., 58 lks.
dist., mkd. T19S R9W S15 BT.

A fir, 36 ins. diam., bears S. 50 1/2° E., 51 lks.
dist., mkd. T19S R9W S22 BT.

A fir, 25 ins. diam., bears S. 4 1/2° W., 25 lks.
dist., mkd. T19S R9W S21 BT.

A fir, 18 ins. diam., bears N. 67° W., 85 lks.
dist., mkd. T19S R9W S16 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, chinquapin,
dogwood, and yew; undergrowth, vine mpale, salal, hazel,
arrowwood, rhododendron, huckleberry, and fern.

From the cor. of secs. 14, 15, 22, and 23.

N. 89° 10' W., bet. secs. 15 and 22.

Ascend 30 ft. along N. slope, through heavy timber and
dense undergrowth.

3.80 Gravelled road, 25 lks. wide, bears N. 70° W. and
S. 80° E.

4.80 Ridge, bears N. 85° W. and S. 85° E.; desc. 140 ft.
along S. slope.

14.50 Gravelled road, 25 lks. wide, bears N. 70° E., And W.
19.30 Leave gravelled road, 25 lks. wide, bears E. and
S. 80° W,

31.90 Same road, 25 lks. wide, bears S. 80° W. and S. 80° E.
in curve.

39.99 Point for the 1/4 sec. cor. of secs. 15 and 22, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins.
in the ground, in a collar of stone, 2 ft. base, to top,
with brass cap mkd.

T 19 S R 9 W
1/4 S 15
S 22
1968

from which

A fir, 23 ins. diam., bears N. 19° W., 19 lks.
dist., mkd. 1/4 S15 BT.

A fir, 15 ins. diam., bears S. 47° W., 65 lks.
dist., mkd. 1/4 S22 BT.