

# County Surveyor's Record, Douglas County, Oregon

15447

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>Corner is located at bottom of descent, slopes S.</p> <p>Ascend 110 ft. over SE. slope.</p>
62.80	<p>Ridge, bears N. 85° E. and S. 85° W.; desc. 165 ft. over NW. slope.</p>
71.60	<p>Bottom of descent, slopes NW.; asc. 10 ft. over NE. slope.</p>
77.00	<p>Spur, slopes N.; desc. 85 ft. over NW. slope, changing to N. slope.</p>
79.98	<p>The cor. of secs. 15, 16, 21, and 22.</p>
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, and chinquapin; undergrowth, salal, vine maple, rhododendron, hazel, arrowwood, and fern.</p>
	<p>N. 2° 06' E., bet. secs. 15 and 16.</p>
	<p>Descend 30 ft. over N. slope, through heavy timber and dense undergrowth.</p>
2.30	<p>Creek, 1 lk. wide, course W.; asc. 120 ft. over broken S. slope.</p>
19.80	<p>Ridge, bears NW. and SE.; desc. 360 ft. over N. slope, changing to NE. slope.</p>
41.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 19 S R 9 W 1/4 S 16   S 15 1968</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 80 1/2° E., 65 lks. dist., mkd. 1/4 S15 BT.</p>
	<p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 44° W., 17 lks. dist., mkd. 1/4 S16 BT.</p>
	<p>Descend 10 ft. over NE. slope.</p>
41.30	<p>Ravine, drains N. 30° W.; desc. 275 ft. along W. slope, changing to broken N. slope.</p>
55.80	<p>Kentucky Creek, 10 lks. wide, course W.; asc. 260 ft. over S. slope.</p>
82.00	<p>Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>