

County Surveyor's Record, Douglas County, Oregon

15448

Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

T 19 S	R 9 W
S 9	S 10
S 16	S 15
1968	

Fd. OK JULY, 1981
LES ROBERTS M 88-21

from which

A fir, 11 ins. diam., bears N. 41° E., 19 lks.
dist., mkd. T19S R9W S10 BT.

A fir, 17 ins. diam., bears S. 30° E., 42 lks.
dist., mkd. T19S R9W S15 BT.

A fir, 22 ins. diam., bears S. 36° W., 26 lks.
dist., mkd. T19S R9W S16 BT.

A fir, 20 ins. diam., bears N. 38° W., 11 lks.
dist., mkd. T19S R9W S9 BT.

Land, mountainous.

Soil, rocky clay.

Timber; fir, hemlock, cedar, maple alder, chinquapin,
and yew; undergrowth, vine maple, salal, rhododendron,
hazel, huckleberry, and fern.

From the cor. of secs. 10, 11, 14, and 15, monumented
with an iron post, 2 1/2 ins. diam., firmly set, projecting
6 ins. above ground, with brass cap mkd.

T 19 S	R 9 W
S 10	S 11
S 15	S 14
1958	

from which bearing trees mkd. in 1958

A fir, 22 ins. diam., bears N. 60° E., 56 lks.
dist., mkd. T19S R9W S11 BT.

A fir, 23 ins. diam., bears S. 39° E., 39 lks.
dist., mkd. T19S R9W S14 BT.

A fir, 15 ins. diam., bears S. 44° W., 30 lks.
dist., mkd. T19S R9W S15 BT.

A fir, 17 ins. diam., bears N. 42 1/2° W., 27 lks.
dist., mkd. T19S R9W S10 BT.

N. 89° 17' W., bet. secs. 10 and 15.

Descend 250 ft. over NW. slope, through heavy timber and
dense undergrowth.

12.90 Ravine, drains N. 20° W.; asc. 170 ft. over NE. slope.

17.10 Spur, slopes N. 30° W.; desc. 420 ft. over W. slope.

32.20 Creek, 2 lks. wide, course N. 10° W.; asc. 270 ft. over
E. slope.

39.34 Point for the 1/4 sec. cor. of secs. 10 and 15, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.