

# County Surveyor's Record, Douglas County, Oregon

15451

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 9 W., Willamette Meridian, Oregon

**CHAINS**

From the cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 19 S R 9 W  
S 32 | S 33  
T 20 S R 9 W  
S 5  
1921

from which the remains of the original bearing trees

A sawed fir stump, 24 ins. diam., bears N. 83° W., 34 lks. dist., with healed balze.

No suitable trees available within limits.

Drive a 6 ft. steel fence post alongside iron post, N. 1° 12' E., bet secs. 32 and 33. Descend 340 ft. over N. slope, through dense brush, across logged area.

7.70 Middle Fork of Smith River, 4 lks. wide, course N. 75° W., also enter timber, edge bears N. 75° W. and S. 75° E.; asc. 345 ft. over SW. slope.

19.00 Spur, slopes W.; desc. 220 ft. over NW. slope.

25.90 Ravine, drains N. 60° W.; asc. 35 ft. over S. slope.

27.20 Spur, slopes W.; desc. 85 ft. over N. slope.

30.30 Creek, 1 lk. wide, course S. 40° W.; asc. 185 ft. over SE. slope.

35.25 Spur, slopes E.; desc. 70 ft. over NE. slope.

39.50 Ravine, drains SE.; asc. 100 ft. over S. slope.

41.90 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4  
S 32 | S 33  
T 19 S | R 9 W  
1969

from which

A cedar, 8 ins. diam., bears S. 33° E., 67 1/2 lks. dist., mkd. 1/4 S33 BT.

A maple, 12 ins. diam., bears N. 40 1/2° W., 58 lks. dist., mkd. 1/4 S32 BT.

Ascend 460 ft. over S. slope.

54.60 Spur ridge, bears NE. and SW.; desc. 500 ft. over SW. slope.

70.00 Ravine, drains W.; asc. 315 ft. over S. slope.