

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T 19 S., R. 9 W., Willamette Meridian, Oregon

15454

CHAINS													
36.40	Spur, slopes S. 55° E.; desc. 100 ft. over NE. slope.												
39.50	Bottom of descent, slopes E.; asc. 55 ft. over S. slope.												
41.89	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">1/4</td><td></td></tr> <tr><td style="text-align: center;">S 29</td><td style="text-align: center;"> </td><td style="text-align: center;">S 28</td></tr> <tr><td style="text-align: center;">T 19 S</td><td></td><td style="text-align: center;">R 9 W</td></tr> <tr><td></td><td style="text-align: center;">1969</td><td></td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A maple, 20 ins. diam., bears S. 48° E., 33 lks. dist., mkd. 1/4 S28 BT.</p> <p style="margin-left: 40px;">A fir, 45 ins. diam., bears S. 65° W., 89 lks. dist., mkd. 1/4 S29 BT.</p> <p>Ascend 280 ft. over S. slope.</p>		1/4		S 29		S 28	T 19 S		R 9 W		1969	
	1/4												
S 29		S 28											
T 19 S		R 9 W											
	1969												
54.00	Spur, slopes S. 55° E.; desc. 110 ft. over NE. slope.												
61.00	Ravine, drains S. 70° E.; asc. 10 ft. over SE. slope.												
62.30	Spur, slopes E.; desc. 180 ft. over N. slope.												
65.90	Ravine, drains E.; asc. 90 ft. over S. slope.												
69.50	Top of ascent, slopes E.; desc. 45 ft. along E. slope.												
83.78	<p>Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="text-align: center;">T 19 S</td><td style="text-align: center;">R 9 W</td></tr> <tr><td style="text-align: center;">S 20</td><td style="text-align: center;">  S 21</td></tr> <tr><td style="text-align: center;">S 29</td><td style="text-align: center;">  S 28</td></tr> <tr><td></td><td style="text-align: center;">1969</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 13 ins. diam., bears N. 38° E., 69 lks. dist., mkd. T19S R9W S21 BT.</p> <p style="margin-left: 40px;">A hemlock, 22 ins. diam., bears S. 69° E., 52 lks. dist. mkd. T19S R9W S28 BT.</p> <p style="margin-left: 40px;">A maple, 20 ins. diam., bears S. 64° W., 33 lks. dist., mkd. T19S R9W S29 BT.</p> <p style="margin-left: 40px;">An alder, 15 ins. diam., bears N. 58° W., 27 lks. dist., mkd. T19S R9W S20 BT.</p> <p>From this point, the closing cor. of secs. 19 and 30, on the W. bdy. of the Tp., bears S. 85° 59' W., 162.83 chs. dist., hereinbefore described in the field notes of the retracement of a portion of the E. bdy., T. 19 S., R 10 W.</p> <p>This control line was fully retraced and careful search</p>	T 19 S	R 9 W	S 20	S 21	S 29	S 28		1969				
T 19 S	R 9 W												
S 20	S 21												
S 29	S 28												
	1969												