

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **15456**  
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Descend 80 ft. over NE. slope, through heavy timber and dense undergrowth.

7.50 Creek, 2 lks. wide, course SE.; asc. 840 ft. over SE. slope.

41.94 Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	1/4	
S 20		S 21
T 19 S		R 9 W
1969		

from which

A fir, 28 ins. diam., bears N. 87 1/2° E., 48 lks. dist., mkd. 1/4 S21 BT.

A fir, 23 ins. diam., bears N. 89° W., 24 lks. dist., mkd. 1/4 S20 BT.

Ascend 10 ft. over SE. slope.

43.60 Top of ascent, slopes E.; desc. 40 ft. over NE. slope.

56.80 Creek, 1 lk. wide, course S. 60° E.; asc. 120 ft. over SE. slope.

71.60 Creek, 2 lks. wide, course E.; asc. 390 ft. over SE. slope.

83.88 Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 19 S R 9 W			
S 17		S 16	
S 20		S 21	
1969			

from which

A fir, 13 ins. diam., bears N. 43° E., 17 lks. dist., mkd. T19S R9W S16 BT.

A fir, 10 ins. diam., bears S. 57 1/2° E., 29 lks. dist., mkd. T19S R9W S21 BT.

A fir, 13 ins. diam., bears S. 41° W., 26 lks. dist., mkd. T19S R9W S20 BT.

A fir, 13 ins. diam., bears N. 66° W., 22 lks. dist., mkd. T19S R9W S17 BT.

From this point, the closing cor. of secs. 18 and 19, on the W. bdy. of the Tp., bears S. 89° 36' W., 159.86 chs. dist., hereinbefore described in the field notes of the retracement of a portion of the E. bdy., T. 19 S., R. 10 W.

FD. OK 12/2/79  
E. ALVARADO 245FS  
C.S. 60/34