

Dependent Resurvey of a Portion of the South Boundary,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

15466

CHAINS

A fir, 52 ins. diam., bears South, 45 lks. dist.,
with healed blaze.

and bearing trees mkd. by Thielsen

A fir, 22 ins. diam., bears N. 42° E., 37 lks.
dist., with healed blaze.

A fir, 29 ins. diam., bears S. 25° E., 48 lks.
dist., with healed blaze.

S. 89° 11' W., beginning new measurement.

Ascend 20 ft. over E. slope, through heavy timber and
light undergrowth.

0.95 Ridge, bears N. 5° E. and S. 5° W., also dirt road, 15
lks. wide, bears same as ridge; desc. 395 ft. over SW.
slope.

14.90 Ravine, drains SW.; desc. 80 ft. over broken SW. slope.

19.46 Point for the W 1/16 sec. cor. of secs. 3 and 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, with brass cap mkd.

$$\begin{array}{r} \text{W } 1/16 \text{ } \frac{\text{S } 34}{\text{S } 3} \\ 1972 \end{array}$$

from which

A fir, 50 ins. diam., bears N. 24° E., 41 lks.
dist., mkd. W 1/16 S34 BT.

A cedar, 28 ins. diam., bears S. 28° E., 68 lks.
dist., mkd. W 1/16 S3 BT.

Descend 340 ft. over SW. slope.

38.92 The cor. of secs. 3, 4, 33, and 34, on S. bdy. of Tp.,
monumented with an iron post, 2½ ins. diam., loosely set,
protruding 12 ins. above ground, with brass cap mkd.

$$\begin{array}{r} \text{T } 31 \text{ S} \\ \frac{\text{S } 33 \text{ S } 34}{\text{S } 4 \text{ S } 3} \\ \text{T } 32 \text{ S } \text{ R } 4 \text{ W} \\ 1959 \end{array}$$

from which the remains of the original bearing trees

A sawed fir stump, 40 ins. diam., bears East, 32
lks. dist., with scribe marks BT visible on
bark. (Record, N. 80° E.)

A fir, 16 ins. diam., bears S. 48° E., 7 lks.
dist., mkd. with healed blaze.

and bearing trees mkd. by Nicklin

A double ash, 11 ins. diam., bears S. 79¼° W., 44
lks. dist., with scribe mark S and other
illegible marks visible on partially healed
blaze. (Record, S. 77° W., 47 lks.)