

Dependent Resurvey of a Portion of the South Boundary,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears S. 80° W., 23 lks. dist.
and bearing trees mkd. by Thielsen

A fir, 20 ins. diam., bears N. 15° E., 129 lks. dist., with healed blaze. (Record, N. 9° E.)

A cedar, 22 ins. diam., bears S. 46° W., 52 lks. dist., with scribe marks $\frac{1}{4}$ S4 BT visible on partially healed blaze. (Record, S. 42 $\frac{1}{2}$ ° W.)

From this point, a witness cor. established and recorded by the County Surveyor, in 1966, bears N. 88° 21' W., 0.358 chs. dist., monumented with an iron pipe, 1 $\frac{1}{2}$ ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 31 S R 4 W
W C
25' East to
 $\frac{1}{4}$ $\frac{S\ 33}{S\ 4}$
T 32 S
1966

from which bearing trees mkd. by the County Surveyor

A fir, 11 ins. diam., bears N. 30 $\frac{1}{4}$ ° W., 46 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears S. 36 $\frac{1}{4}$ ° E., 8 $\frac{1}{2}$ lks. dist., with healed blaze.

S. 88° 38' W., beginning new measurement.

Ascend 40 ft. over nearly level land, across open field.

1.25 Cow Creek Road, paved, 30 lks. wide, bears N. 10° E. and S. 30° W., in curve.

9.70 Leave open field, enter scattered timber and dense undergrowth, edge bears N. 20° W. and S. 20° E.; asc. 225 ft. over broken NE. slope.

19.87 Point for the W 1/16 sec. cor. of secs. 4 and 33.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 33}{S\ 4}$
1972

from which

A fir, 6 ins. diam., bears N. 1° W., 46 lks. dist., mkd. W 1/16 S33 BT.

A fir, 13 ins. diam., bears S. 88° W., 41 $\frac{1}{2}$ lks. dist., mkd. W 1/16 S4 BT.

Ascend 105 ft. over broken NE. slope.

25.55 Ravine, drains SE.; asc. 300 ft. over broken NE. slope.