

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

15470

CHAINS	
	<p>(Restoring the survey executed by William H. Byars, U. S. Deputy Surveyor, in 1871, and the retracement executed by William M. Bushey, U. S. Deputy Surveyor, in 1894)</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on S. bdy. of Tp.</p> <p>N. 1° 06' W., bet. secs. 34 and 35, marking and blazing the true line.</p> <p>Ascend 85 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
14.20	Cow Creek Road, paved, 30 lks. wide, bears N. 10° W. and S. 10° E.
19.65	Spur, slopes W.; desc. 120 ft. over NW. slope.
25.90	Cow Creek Road, paved, 30 lks. wide, bears NE. and SW.
30.65	Cow Creek, 80 lks. wide, course S. 80° E.; asc. 335 ft. over S. slope.
39.96	Point for the ¼ sec. cor. of secs. 34 and 35, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 31 S R 4 W</p> <p style="margin-left: 100px;">¼</p> <p style="margin-left: 100px;">S 34 S 35</p> <p style="margin-left: 100px;">1972</p>
	from which
	A fir, 8 ins. diam., bears N. 55° E., 62½ lks. dist., mkd. ¼ S35 BT.
	A ponderosa pine, 18 ins. diam., bears S. 75° W., 107½ lks. dist., mkd. ¼ S34 BT.
	<hr/>
	N. 1° 35' W., beginning new measurement.
	Ascend 5 ft. over S. slope.
0.95	Spur, slopes N. 80° E.; desc. 355 ft. over N. slope.
10.50	Cow Creek, 80 lks. wide, course West; asc. 160 ft. over SW. slope.
18.40	Cow Creek Road, paved, 30 lks. wide, bears N. 60° W. and S. 60° E.
26.60	Wet ravine, drains S. 50° W.; asc. 130 ft. over S. slope.
39.73	The cor. of secs. 26, 27, 34, and 35, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, subsequently perpetuated and recorded by the County Surveyor, in 1966, monumented with an iron pipe, 1 in. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.