

15471

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 31 S R 4 W

S 27 | S 26

S 34 | S 35

1966

from which the remains of the original bearing trees

A fir, 15 ins. diam., bears N. 75° E., 39 lks.
dist., with scribe marks 6S visible on partially
opened upper blaze and with healed lower blaze.

A cedar, 17 ins. diam., bears S. 42° E., 35 lks.
dist., with healed double blaze. (Record,
S. 40° E.)

A sawed fir stump, 60 ins. diam., bears S. 43° W.,
53½ lks. dist., no marks visible. (Record,
S. 35° W., 51 lks.)

A fir, 32 ins. diam., bears N. 57¼° W., 38 lks.
dist., with healed double blaze. (Record,
N. 62° W., 36 lks.)

and bearing trees mkd. by Wenderoth

A fir, 15 ins. diam., bears N. 50° E., 85 lks.
dist., with healed blaze.

A fir, 15 ins. diam., bears S. 81¼° E., 76 lks.
dist., with healed blaze.

A cedar, 13 ins. diam., bears S. 58¾° W., 53 lks.
dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, madrone, alder, maple, and dogwood;
undergrowth, poison oak, Oregon grape, willow, vine
maple, salal, and manzanita.

N. 0° 35' W., bet. secs. 26 and 27.

Ascend 70 ft. over SW. slope, through heavy timber and
dense undergrowth.

5.10 Spur, slopes S. 70° W.; desc. 20 ft. over NW. slope.

7.45 Ravine, drains S. 70° W.; asc. 95 ft. over SW. slope.

13.50 Spur, slopes S. 70° W.; desc. 140 ft. over NW. slope.

20.12 Point for the S 1/16 sec. cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S 1/16

S 27 | S 26

1972

from which

A fir, 5 ins. diam., bears S. 36° E., 32 lks.
dist., mkd. S 1/16 S26 BT.