

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

15472

CHAINS	
	<p>A fir, 12 ins. diam., bears S. $61\frac{1}{2}^{\circ}$ W., 123 lks. dist., mkd. S 1/16 S27 BT.</p> <p>Descend 45 ft. over NW. slope, across partially logged area.</p>
23.30	Wet ravine, drains S. 70° W.; asc. 80 ft. over SW. slope.
27.25	Spur, slopes S. 70° W.; desc. 30 ft. over NW. slope.
29.15	Wet ravine, drains W.; desc. 25 ft. along W. slope.
37.80	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
40.24	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 S R 4 W $\frac{1}{4}$ S 27 S 26 1972</p> <p>from which</p> <p>A fir, 22 ins. diam., bears S. $64\frac{3}{4}^{\circ}$ E., 97 lks. dist., mkd. $\frac{1}{4}$ S26 BT.</p> <p>A fir, 27 ins. diam., bears S. $7\frac{1}{4}^{\circ}$ W., $134\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S27 BT.</p> <p>From this point, a local corner established by George J. Wenderoth, Deputy County Surveyor, based on single proportionate method, bears S. $50^{\circ} 18'$ W., 0.395 chs. dist., determined from the remains of bearing trees mkd. by Wenderoth:</p> <p>A root hole, bears N. $61^{\circ} 43'$ W., 54 lks. dist., with a down yew alongside, 10 ins. diam., with scribe marks $\frac{1}{4}$ S CS BT visible on open double blaze.</p> <p>This corner position was not accepted because it failed to protect the 1894 William Bushey record, which returned an irregular boundary.</p> <p style="text-align: center;">—————</p> <p>N. $1^{\circ} 16'$ W., beginning new measurement.</p> <p>Descend 5 ft. over NW. slope.</p>
5.70	McGinnis Creek, 5 lks. wide, course S. 15° W.; asc. 130 ft. over broken SE. slope.
14.95	Wet ravine, drains S. 60° E.; asc. 255 ft. over SE. slope.
35.60	Wet ravine, drains S. 60° E.; asc. 135 ft. over SE. slope.
39.81	The cor. of secs. 22, 23, 26, and 27, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, from original evidence no longer in existence, subsequently perpetuated and recorded by the County Surveyor, in 1966, monumented with an iron pipe, 1 in. diam. firmly set, protruding 12 ins. above ground, with brass cap mkd.