

15475

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>and bearing trees mkd. by Eppstein</p> <p>A fir, 12 ins. diam., bears N. 20° E., 32½ lks. dist., with healed double blaze.</p> <p>A fir, 19 ins. diam., bears S. 82¾° E., 30 lks. dist., with healed double blaze.</p> <p>A fir, 22 ins. diam., bears S. 56¾° W., 53½ lks. dist., with healed double blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, madrone, oak, maple, and chinquapin; undergrowth, manzanita, blackberry, huckleberry, salal, Oregon grape, poison oak, and arrowwood.</p>
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 89° 14' W., bet. secs. 27 and 34.</p> <p>Descend 210 ft. over SW. slope, through scattered timber and light undergrowth.</p>
19.86	Irrigation ditch, 2 lks. wide, drains S. 20° W.
19.91	<p>The E 1/16 sec. cor. of secs. 27 and 34, established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1958, monumented with an iron pipe, 1 in. diam., firmly set, protruding 8 ins. above ground, from which bearing trees mkd. by Wenderoth:</p> <p>A ponderosa pine, 10 ins. diam., bears N. 72¾° E., 138 lks. dist., with healed blaze.</p> <p>A madrone, 17 ins. diam., bears N. 20½° W., 146 lks. dist., with scribe marks S /16 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 <math>\frac{S\ 27}{S\ 34}</math> 1972</p>
	<p>S. 89° 17' W., beginning new measurement.</p> <p>Descend 85 ft. over W. slope, across open pasture land.</p>
19.80	Cow Creek Road, paved, 30 lks. wide, bears N. and S.
20.02	<p>The ¼ sec. cor. of secs. 27 and 34, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, from original evidence no longer in existence, subsequently perpetuated and recorded by James Byron, Deputy County Surveyor, in 1956, monumented with an iron pipe, 1½ ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.</p>