

15477

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
1.60	<p>N. 1° 03' W., bet. secs. 27 and 28.</p> <p>Ascend 2 ft. over SE. slope, through heavy timber and moderate undergrowth.</p>
20.04	<p>Spur, slopes NE.; desc. 500 ft. over NW. slope.</p> <p>Point for the S 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 28   S 27 1972</p>
35.45	<p>from which</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears S. 29½° E., 42 lks. dist., mkd. S 1/16 S27 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 63° W., 13 lks. dist., mkd. S 1/16 S28 BT.</p> <p>Descend 105 ft. over NW. slope.</p> <p>Leave timber and undergrowth, enter open pasture land, edge bears N. 70° E. and S. 70° W.</p>
40.08	<p>The ¼ sec. cor. of secs. 27 and 28, reestablished and recorded based on proportionate method by George J. Wenderoth, Deputy County Surveyor, in 1947, monumented with an iron pipe, 1 in. diam., firmly set, the top 8 ins. below the surface of the ground, from which a bearing tree mkd. by Wenderoth:</p> <p style="padding-left: 40px;">An ash, 18 ins. diam., bears N. 84° E., 271 lks. dist., with scribe marks ¼ C BT visible on partially healed double blaze.</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1956</p> <p style="padding-left: 40px;">A triple maple, 72 ins. diam., bears N. 36½° W., 618 lks. dist., with scribe marks CS BT S28 visible on partially healed double blaze.</p> <p>and a bearing tree and bearing object mkd. by the County Surveyor, in 1966</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 68½° E., 770 lks. dist., mkd. with healed double blaze.</p> <p style="padding-left: 40px;">A power pole, Number E 1510, bears N. 89½° W., 30½ lks. dist.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., the top 8 ins. below the surface of the ground and directly over iron pipe, with brass cap mkd.</p>
	<p style="text-align: center;">T 31 S R 4 W ¼ S 28   S 27 1972</p>