

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	N. 1° 00' W., beginning new measurement.
	Descend 10 ft. over N. slope, across open pasture land.
4.00	Cow Creek, 50 lks. wide, course NW.; asc. 110 ft. over S. slope.
6.70	Cow Creek Road, paved, 30 lks. wide, bears NW. and SE.
19.99	The N 1/16 sec. cor. of secs. 27 and 28, established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, monumented with an iron pipe, 1 in. diam., firmly set, protruding 4 ins. above ground, from which bearing trees mkd. by Wenderoth:
	A fir, 13 ins. diam., bears N. 20° E., 115 lks. dist., with healed double blaze.
	A fir, 28 ins. diam., bears N. 77° W., 222 lks. dist., with healed double blaze.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.
	N 1/16 S 28   S 27 1972
	From this point, a local corner, established by person(s) unknown, bears N. 3½° W., 57½ lks. dist., monumented with an iron bolt, 1 in. diam., with 1½ ins. squared head, firmly set, protruding 9 ins. above ground.
	N. 1° 02' W., beginning new measurement.
	Ascend 235 ft. over SE. slope, through scattered timber and dense undergrowth.
11.15	Spur, slopes S. 30° W.; desc. 145 ft. over NW. slope.
19.95	The cor. of secs. 21, 22, 27, and 28, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, subsequently perpetuated and recorded by the County Surveyor, in 1966, monumented with an iron pipe, 1½ ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 31 S R 4 W 21   22 28   27 1966
	from which the remains of bearing trees mkd. by Bushey
	A fir, 24 ins. diam., bears S. 14½° W., 31 lks. dist., with scribe marks S2 visible on partially open blaze.
	and bearing trees mkd. by Wenderoth
	A hemlock, 15 ins. diam., bears N. 5° E., 81 lks. dist., with healed double blaze.