

15479

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A yew, 11 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ E., 70 lks. dist., with scribe marks S27 CS BT visible on open double blaze.</p> <p>A fir, 32 ins. diam., bears N. 33° W., 92 lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by the County Surveyor</p> <p>A yew, 10 ins. diam., bears S. $25\frac{1}{2}^{\circ}$ W., $67\frac{1}{2}$ lks. dist., with scribe marks T31S R4W S28 CS BT visible on open double blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, madrone, maple, alder, and chinquapin; undergrowth, salal, rhododendron, manzanita, huckleberry, hazel, arrowwood, fern, and vine maple.</p>
	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>S. $89^{\circ} 40'$ W., bet. secs. 22 and 27.</p> <p>Ascend 80 ft. over SE. slope, through scattered timber and dense undergrowth, across logged area.</p>
0.45	Dirt road, 25 lks. wide, bears NE. and SW.
5.25	Spur ridge, bears N. and S., also leave logged area and enter heavy timber and dense undergrowth, edge bears same as ridge; desc. 310 ft. over SW. slope.
19.96	<p>The E $\frac{1}{16}$ sec. cor. of secs. 22 and 27, established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1960, monumented with an iron pipe, 1 in. diam., firmly set, protruding 12 ins. above ground, from which bearing trees mkd. by Wenderoth.</p> <p>A madrone, 19 ins. diam., bears N. 53° E., 33 lks. dist., with scribe marks $\frac{1}{16}$ S CS BT visible on partially healed double blaze.</p> <p>A chinquapin, 6 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ E., 36 lks. dist., with scribe marks $\frac{1}{16}$ S CS BT visible on partially healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;"> $E \frac{1}{16} \begin{array}{l} S \ 22 \\ S \ 27 \end{array}$ 1972 </p>
	<p>S. $89^{\circ} 34'$ W., beginning new measurement.</p> <p>Descend 145 ft. over SW. slope.</p>
4.80	Creek, 1 lk. wide, course S. 10° W.; asc. 25 ft. over SE. slope.
8.05	Spur, slopes S.; desc. 10 ft. over SW. slope.