

15480

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
9.15	Ravine, drains S. 10° E.; asc. 40 ft. over SE. slope.
12.70	Spur, slopes S.; desc. 50 ft. over SW. slope.
15.80	Ravine, drains S.; asc. 65 ft. over SE. slope.
19.89	The ¼ sec. cor. of secs. 22 and 27, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, subsequently perpetuated and recorded by the County Surveyor, in 1966, monumented with an iron pipe, 1½ ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 31 S R 4 W ¼ $\frac{S 22}{S 27}$ 1966
	from which the original bearing trees
	A fir, 25 ins. diam., bears N. 62° E., 15 lks. dist., with healed double blaze.
	A fir, 22 ins. diam., bears S. 25° W., 6 lks. dist., with scribe mark S visible on partially opened double blaze.
	—————
	S. 88° 56' W., beginning new measurement.
	Ascend 25 ft. over SE. slope, through heavy timber and dense undergrowth.
5.55	Spur ridge, bears NE. and SW.; desc. 425 ft. over NW. slope.
19.00	Dirt road, 15 lks. wide, bears NE. and SW.
19.92	The W 1/16 sec. cor. of secs. 22 and 27, established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, monumented with an iron pipe, 1 in. diam., firmly set, protruding 10 ins. above ground, from which the remains of bearing trees mkd. by Wenderoth:
	A root hole, bears N. 36½° E., 93½ lks. dist., with a down yew alongside, 20 ins. diam., with scribe marks 1/16 S CS BT visible on partially healed double blaze.
	A yew, 13 ins. diam., bears N. 44° W., 44½ lks. dist., with scribe marks 1/16 S CS BT visible on partially healed double blaze.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.
	W 1/16 $\frac{S 22}{S 27}$ 1972
	from which a new bearing tree
	A hemlock, 9 ins. diam., bears S. 12½° W., 46½ lks. dist., mkd. W 1/16 S27 BT.
	—————