

Dependent Resurvey, Portion of Subdivisional Lines, **15484**
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
1.20	Top of knoll on spur ridge, bears N. and S.; desc. 340 ft. over SW. slope.
20.15	<p>The E 1/16 sec. cor. of secs. 28 and 33, established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1949, monumented with an iron pipe, 1 in. diam., firmly set, protruding 12 ins. above ground, from which bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A twin madrone, 8 ins. diam., bears N. 84° E., 18½ lks. dist., with scribe mark S visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A madrone, 9 ins. diam., bears S. 27° W., 20½ lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \text{E } 1/16 \text{ } \frac{\text{S } 28}{\text{S } 33} \\ 1972 \end{array}$ </div> <p>S. 89° 59' W., beginning new measurement.</p> <p>Descend 290 ft. over SW. slope, through scattered timber and dense undergrowth.</p>
19.15	Leave timber and undergrowth, enter open field, edge bears NW. and SE.
20.13	<p>The ¼ sec. cor. of secs. 28 and 33, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, from original evidence no longer in existence, subsequently perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, and perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1956, monumented with an iron post, 1½ ins. diam., firmly set, protruding 6 ins. above ground, in a mound of stone, 1 ft. base, 6 ins. high, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 31 S R 4 W</p> $\frac{\text{S } 28}{\text{S } 33}$ <p>¼ COR.</p> <p>1956</p> </div> <p>from which a bearing tree recorded by Stewart</p> <p style="padding-left: 40px;">A white fir snag, 40 ins. diam., bears N. 19½° W., 170 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Ben B. Irving, Registered Engineer No. 240, in 1937</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 29½° E., 51 lks. dist., with scribe marks BT visible on open lower blaze and with healed upper blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears N. 82½° E., 103 lks. dist., with healed double blaze.</p>