

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

15486

CHAINS 32.75	Creek, 1 lk. wide, course S. 60° E.; asc. 60 ft. over SE. slope.
42.64	The ¼ sec. cor. of secs. 28 and 29, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1949, subsequently perpetuated and recorded by the County Surveyor, in 1966, monumented with an iron pipe, 1½ ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE ¼ S 29 S 28 1966
	from which original bearing trees
	A fir, 24 ins. diam., bears S. 77¾° E., 49 lks. dist., with healed blaze. (Record, S. 75° E.) This tree was rescribed by the County Surveyor, in 1966, with scribe marks S28 CS BT visible on partially healed blaze.
	A fir, 51 ins. diam., bears N. 25° W., 10 lks. dist., with healed blaze. (Record, N. 28° W.)
	N. 0° 42' E., beginning new measurement.
	Ascend 225 ft. over SE. slope, through heavy timber and dense undergrowth.
13.70	Spur, slopes S. 60° E.; desc. 190 ft. over NE. slope.
19.36	From this point, a local corner established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1949, bears West, 0.04 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set, protruding 12 ins. above ground, from which the remains of bearing trees mkd. by Wenderoth
	A root hole, bears S. 78° E., 67 lks. dist., with a down yew alongside, 12 ins. diam., with scribe marks 1/16 S CS BT visible on partially healed double blaze.
	A fir, 50 ins. diam., bears N. 36½° W., 57 lks. dist., with healed double blaze.
	Descend 70 ft. over NE. slope.
21.85	Creek, 3 lks. wide, course SE.; asc. 505 ft. over S. slope.
27.35	Dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.
37.10	Spur, slopes S. 80° E.; desc. 20 ft. over NE. slope.
38.83	The cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1949, subsequently perpetuated and recorded by the County Surveyor, in 1966, monumented with an iron pipe, 1½ ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE S 20 S 21 S 29 S 28 1966