

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
21.30	Spur, slopes S. 20° W.; desc. 255 ft. over SW. slope.
30.50	Creek, 3 lks. wide, course S. 20° E.; asc. 280 ft. over general E. slope.
38.28	The ¼ sec. cor. of secs. 21 and 28, perpetuated and recorded by the County Surveyor, in 1966, monumented with an iron pipe, 1½ ins. diam., firmly set, protruding 20 ins. above ground, with a yew post, 4 ins. square, firmly set, protruding 24 ins. above ground, mkd. with ¼ S CS on E., S21 on N., and S28 on S. faces, alongside, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 31 S R 4 W ¼ $\frac{S\ 21}{S\ 28}$ 1966
	from which the remains of bearing trees mkd. by Bushey
	A burned and decayed fir snag, 18 ins. diam., bears N. 63¾° W., 38½ lks. dist., with burned and decayed blaze. (Record, N. 60° E.)
	and bearing trees mkd. by Ben B. Irving, Registered Engineer No. 240, in 1937, and rescribed by the County Surveyor, in 1966
	A fir, 28 ins. diam., bears N. 36° W., 53 lks. dist., with scribe marks ¼ S21 C visible on bark blaze and with healed double blaze.
	A fir, 38 ins. diam., bears S. 71½° E., 56 lks. dist., with healed double blaze.

	S. 89° 07' W., beginning new measurement.
	Ascend 80 ft. over E. slope, through heavy timber and dense undergrowth.
3.55	Spur, slopes S.; desc. 245 ft. over SW. slope.
13.00	Ravine, drains S. 40° W.; asc. 20 ft. along S. slope.
16.70	Top of ascent, slopes S.; desc. 140 ft. over SW. slope.
22.55	Ravine, drains S. 60° W.; desc. 95 ft. over SW. slope.
29.00	Creek, 5 lks. wide, course S. 20° E.; asc. 390 ft. over NE. slope.
38.74	The cor. of secs. 20, 21, 28, and 29.
	Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, madrone, chinquapin, alder, maple, and dogwood; undergrowth, Oregon grape, poison oak, salal, huckleberry, rhododendron, manzanita, fern, and arrowwood.
	Subdivision of Section 27, T. 31 S., R. 4 W., Willamette Meridian, Oregon
	From the ¼ sec. cor. of secs. 27 and 34.