

Subdivision of Section 27, T. 31 S., R. 4 W.,
Willamette Meridian, Oregon

15490

CHAINS	
	<p>This corner point was not accepted because its position is based on Wenderoth's $\frac{1}{4}$ section corner of sections 26 and 27 which was not utilized.</p> <p>Ascend 70 ft. over SW. slope, through scattered timber and dense undergrowth.</p> <p>54.95 Creek, 1 lk. wide, course SW.; asc. 45 ft. over SW. slope.</p> <p>58.80 Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.</p> <p>60.14 Point for the center N 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C N 1/16 S 27 C 1972</p> </div> <p>from which a bearing tree mkd. by George J. Wenderoth, Deputy County Surveyor, in 1947</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 63½° W., 29½ lks. dist., with scribe marks 1/16 SC visible on open blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 82° E., 260½ lks. dist., mkd. CN 1/16 S27 BT.</p> <p>From this point, a local corner established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, bears S. 56½° W., 0.085 chs. dist., monumented with a broken and bent iron pipe, 1 in. diam., loosely set, protruding 4 ins. above ground. This corner point was not accepted because its position is based on Wenderoth's $\frac{1}{4}$ section corner of sections 26 and 27 which was not utilized.</p> <p>Ascend 330 ft. over S. slope.</p> <p>80.20 The $\frac{1}{4}$ sec. cor. of secs. 22 and 27.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.</p> <p>S. 89° 07' W., on the E. and W. center line of sec. 27.</p> <p>Descend 20 ft. over SW. slope, through scattered timber and dense undergrowth.</p> <p>1.70 McGinnis Creek, 5 lks. wide, course S. 20° W.; asc. 195 ft. over SE. slope.</p> <p>8.10 Spur, slopes S. 10° W.; desc. 270 ft. over W. slope.</p> <p>20.06 Point for the center E 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16 C S 27 C 1972</p> </div>