

098

15491

Subdivision of Section 27, T. 31 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS	
	<p>from which bearing trees mkd. by George J. Wenderoth, Deputy County Surveyor, in 1947</p> <p>A fir, 20 ins. diam., bears S. <math>75\frac{1}{2}^{\circ}</math> E., 68 lks. dist., with healed blaze.</p> <p>A fir, 22 ins. diam., bears S. <math>30\frac{1}{2}^{\circ}</math> W., 110 lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p>A fir, 15 ins. diam., bears N. <math>24\frac{1}{2}^{\circ}</math> E., <math>61\frac{1}{2}</math> lks. dist., mkd. CE 1/16 S27 BT.</p> <p>From this point, a local corner established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1947, bears S. <math>49^{\circ} 20'</math> W., 0.255 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, protruding 14 ins. above ground. This corner point was not accepted because its position is based on Wenderoth's <math>\frac{1}{2}</math> section corner of sections 26 and 27 which was not utilized.</p> <p>Descend 75 ft. over SW. slope.</p>
26.15	Creek, 1 lk. wide, course S. $60^{\circ}$ W.; desc. 55 ft. over SW. slope.
40.12	The center $\frac{1}{2}$ sec. cor. of sec. 27.
	Descend 50 ft. over SW. slope.
60.00	Point for the center W 1/16 sec. cor. of sec. 27.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\frac{W\ 1/16}{S\ 27}C$ 1972
	<p>from which a bearing tree mkd. by George J. Wenderoth, Deputy County Surveyor, in 1947</p> <p>A sawed ponderosa pine stump, 38 ins. diam., bears N. <math>60\frac{1}{2}^{\circ}</math> E., <math>182\frac{1}{2}</math> lks. dist., with scribe marks 1/16 S CS visible on burned and decayed open blaze.</p> <p>and a bearing tree of no record</p> <p>A white oak, 15 ins. diam., bears N. <math>62\frac{1}{2}^{\circ}</math> E., 191 lks. dist., with healed double blaze.</p> <p>and new bearing trees</p> <p>A ponderosa pine, 12 ins. diam., bears N. <math>37^{\circ}</math> W., 158 lks. dist., mkd. CW 1/16 S27 BT.</p> <p>A ponderosa pine, 14 ins. diam., bears S. <math>50\frac{1}{2}^{\circ}</math> E., 416 lks. dist., mkd. CW 1/16 S27 BT.</p> <p>Descend 35 ft. over SW. slope.</p>
60.60	Dirt road, 20 lks. wide, bears N. and S.
73.30	Cow Creek Road, paved, 30 lks. wide, bears N. $55^{\circ}$ W. and S. $55^{\circ}$ E.