

Subdivision of Section 27, T. 31 S., R. 4 W., **15492**
Willamette Meridian, Oregon

CHAINS	
75.90	Cow Creek, 80 lks. wide, course N. 55° W.; asc. 15 ft. over NE. slope.
79.88	The ½ sec. cor. of secs. 27 and 28.
	<p>From the E 1/16 sec. cor. of secs. 27 and 34.</p> <p>N. 0° 51' W., on the N. and S. center line of the SE¼ of sec. 27.</p> <p>Descend 15 ft. over N. slope, through scattered timber and dense undergrowth.</p> <p>2.15 McGinnis Creek, 4 lks. wide, course S. 80° W.; asc. 190 ft. over SE. slope.</p> <p>3.65 Dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.</p> <p>9.50 Spur, slopes SW.; desc. 135 ft. along broken W. slope.</p> <p>27.00 Bottom of descent, slopes W.; asc. 65 ft. over broken SW. slope.</p> <p>38.00 Top of ascent, slopes W.; desc. 10 ft. over NW. slope.</p> <p>40.12 The center E 1/16 sec. cor. of sec. 27.</p>
	<p>From the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>N. 0° 56' W., on the N. and S. center line of the SW¼ of sec. 27.</p> <p>Ascend 10 ft. along E. slope, through heavy timber and dense undergrowth.</p> <p>1.60 Top of ascent, slopes E.; desc. 20 ft. along E. slope.</p> <p>4.00 Bottom of descent, slopes E.; asc. 75 ft. along E. slope.</p> <p>10.00 Top of ascent, slopes E.; desc. 135 ft. over NE. slope.</p> <p>14.15 Bottom of steep descent; desc. 5 ft. over nearly level ground.</p> <p>15.15 Leave timber and undergrowth; enter open field, edge bears NW. and SE.</p> <p>20.04 Point for the SW 1/16 sec. cor. of sec. 27, at intersection with the E. and W. center line of the SW¼ of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 27 1972</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 69¾° W., 257 lks. dist., mkd. SW 1/16 S27 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 89° W., 260 lks. dist., mkd. SW 1/16 S27 BT.</p>