100

15493

Subdivision of Section 27, T. 31 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
	Set a 5 ft. steel fence post alongside iron post.
	Descend 20 ft. over NE. slope.
27.35	Gravelled driveway, 15 lks. wide, bears N. 70° W. and S. 70° E.
28.30	Cow Creek, 50 lks. wide, course N. 70° W.; asc. 40 ft. over S. slope.
29.55	Cow Creek Road, paved, 30 lks. wide, bears N. 70° W. and S. 70° E.
40.09	The center W 1/16 sec. cor. of sec. 27.
	From the center S 1/16 sec. cor. of sec. 27.
	S. 89° 08' W., on the E. and W. center line of the SW¼ of sec. 27.
	Descend 40 ft. over SW. slope, across open field.
1.90	Cow Creek Road, paved, 30 lks. wide, bears N. 30° W. and S. 30° E.
6.95	Cow Creek, 50 lks. wide, course N. 15° W.; asc. 15 ft. over nearly level land.
19.86	The SW 1/16 sec. cor. of sec. 27.
21.95	Leave open field, enter scattered timber and dense undergrowth, edge bears NW. and SE.; asc. 205 ft. over NE. slope.
28.00	Spur, slopes N. 10° W.; desc. 110 ft. over NW. slope.
39.71	The S 1/16 sec. cor. of secs. 27 and 28.
	From the center W 1/16 sec. cor. of sec. 27.
	N. 0° 57' W., on the N. and S. center line of the NW¼ of sec. 27.
	Ascend 110 ft. over SW. slope, through scattered timber and dense undergrowth.
0.70	Dirt road, 20 lks. wide, bears N. 35° E. and S. 35° W.
13.45	Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.
20.04	Point for the NW 1/16 sec. cor. of sec. 27, at intersection with the E. and W. center line of the NW¼ of sec. 27.
	Set an iron post, 28 ins. long, 2½ ins. diam.,24 ins. in the ground, with brass cap mkd.
	NW 1/16 S 27 1972
	from which the remains of bearing trees mkd. by George J. Wenderoth, Deputy Sounty Surveyor, in 1947