

15495

Subdivision of Section 28, T. 31 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS 20.43	<p>Point for the center S 1/16 sec. cor. of sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 28 C 1972</p> <p>from which</p> <p>A fir, 20 ins. diam., bears N. 36½° E., 29½ lks. dist., mkd. CS 1/16 S28 BT.</p> <p>A fir, 12 ins. diam., bears S. 6¾° W., 71 lks. dist., mkd. CS 1/16 S28 BT.</p> <p>Ascend 25 ft. along W. slope.</p>
27.90	<p>Top of ascent, slopes W.; desc. 160 ft. along W. slope.</p>
40.86	<p>Point for the center ¼ sec. cor. of sec. 28, at intersection with the E. and W. center line of sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C ¼ S 28 1972</p> <p>from which</p> <p>A fir, 22 ins. diam., bears N. 73° E., 13 lks. dist., mkd. C¼ S28 BT.</p> <p>A fir, 21 ins. diam., bears S. 16° W., 57½ lks. dist., mkd. C¼ S28 BT.</p> <p>Descend 50 ft. over NW. slope.</p>
46.50	<p>Cow Creek, 70 lks. wide, course N. 70° W.; asc. 430 ft. over SW. slope.</p>
47.50	<p>Cow Creek Road, paved, 30 lks. wide, bears N. 70° W. and S. 70° E.</p>
60.95	<p>Point for the center N 1/16 sec. cor. of sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 28 C 1972</p> <p>from which</p> <p>A fir, 15 ins. diam., bears S. 5° E., 70 lks. dist., mkd. CN 1/16 S28 BT.</p> <p>A fir, 49 ins. diam., bears N. 89½° W., 52 lks. dist., mkd. CN 1/16 S28 BT.</p> <p>Ascend 245 ft. over SW. slope.</p>