


Subdivision of Section 28, T. 31 S., R. 4 W.,  
Willamette Meridian, Oregon

15496

CHAINS	
75.35	Spur, slopes S. 30° E.; desc. 10 ft. over NE. slope.
81.04	The ¼ sec. cor. of secs. 21 and 28.
	From the ¼ sec. cor. of secs. 27 and 28.
	N. 88° 48' W., on the E. and W. center line of sec. 28.
	Descend 15 ft. over nearly level land, across open field.
19.30	Cow Creek, 70 lks. wide, course S. 40° W.; asc. slightly over SE. slope.
19.63	True point for the center E 1/16 sec. cor. of sec. 28, falls in Cow Creek, where it is impracticable to establish a permanent monument.
	Ascend 20 ft. over SE. slope.
20.63	Point selected for the witness corner to the center E 1/16 sec. cor. of sec. 28.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	WC  WC → E 1/16 C S 28 C 1972
	from which
	The center of a metal underground telephone cable box, 6 ins. square, 28 ins. high, bears N. 29½° E. 19 lks. dist.
	A fir, 11 ins. diam., bears S. 46° W., 239 lks. dist., mkd. X WC BT.
	Ascend 30 ft. over SE. slope.
21.05	Cow Creek Road, paved, 30 lks. wide, bears N. 40° E. and S. 50° W., in curve.
22.30	Spur, slopes S.; desc. 55 ft. over SW. slope.
26.20	Cow Creek Road, paved, 30 lks. wide, bears N. 60° W. and S. 60° E.
29.30	Cow Creek, 70 lks. wide, course N. 35° W.; asc. 65 ft. over NE. slope.
37.70	Spur, slopes N.; desc. 20 ft. over NW. slope.
39.26	The center ¼ sec. cor. of sec. 28.
	Descend 75 ft. over NW. slope.
52.75	Cow Creek, 50 lks. wide, course S. 40° E.; asc. 210 ft. over SE. slope.
54.15	Cow Creek Road, paved, 30 lks. wide, bears N. 10° W. and S. 10° E.
78.26	The ¼ sec. cor. of secs. 28 and 29.