

15497

Subdivision of Section 28, T. 31 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
	From the true point for the center E 1/16 sec. cor. of sec. 28.
	N. 0° 20' W., on the N. and S. center line of the NE¼ of sec. 28.
	Across Cow Creek, course S. 40° W.
0.05	Leave Cow Creek, edge bears N. 40° E. and S. 40° W.; asc. 390 ft. over SE. slope, through scattered timber and dense undergrowth.
1.75	Cow Creek Road, paved, 30 lks. wide, bears N. 40° E. and S. 40° W.
17.60	Spur, slopes E.; desc. 75 ft. over N. slope.
20.07	Point for the NE 1/16 sec. cor. of sec. 28, at intersection with the E. and W. center line of the NE¼ of sec. 28.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NE 1/16 S 28 1972
	from which
	A fir, 17 ins. diam., bears N. 81° E., 48 lks. dist., mkd. NE 1/16 S28 BT.
	A yew, 9 ins. diam., bears S. 76° W., 132½ lks. dist., mkd. NE 1/16 S28 BT.
	Descend 140 ft. over N. slope.
23.45	Creek, 3 lks. wide, course N. 70° E.; asc. 410 ft. over SE. slope.
40.11	The E 1/16 sec. cor. of sec. 28 only.
	From the N 1/16 sec. cor. of secs. 27 and 28.
	N. 88° 38' W., on the E. and W. center line of the NE¼ of sec. 28.
	Descend 60 ft. along S. slope, through scattered timber and dense undergrowth.
7.10	Creek, 1 lk. wide, course S. 10° W.; asc. 280 ft. over E. slope.
17.70	Top of ascent, slopes N.; desc. 10 ft. along N. slope.
19.38	The NE 1/16 sec. cor. of sec. 28.
	Descend 20 ft. along N. slope.
21.65	Ravine, drains N.; asc. 245 ft. over general NE. slope.
34.00	Spur, slopes S. 20° E.; desc. 135 ft. over SW. slope.
38.75	The center N 1/16 sec. cor. of sec. 28.