

15499

Subdivision of Section 33, T. 31 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS	
	<p>N. 2° 07' W., on the N. and S. center line of sec. 33.</p> <p>Ascend 20 ft. along E. slope, through scattered timber and light undergrowth.</p>
5.85	<p>Cow Creek Road, paved, 30 lks. wide, bears N. 10° E. and S. 10° W.</p>
19.95	<p>Point for the center S 1/16 sec. cor. of sec. 33.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">C S 1/16   S 33 C 1972</p>
	<p>from which</p>
	<p>A fir, 10 ins. diam., bears S. 86° W., 312 lks. dist., mkd. CS 1/16 S33 BT.</p>
	<p>A fir, 6 ins. diam., bears N. 60¾° W., 281 lks. dist., mkd. CS 1/16 S33 BT.</p>
	<p>From this point, a local corner established by person(s) unknown, bears N. 88° 48' W., 0.235 chs. dist., monumented with an iron pipe, 1¼ ins. diam., firmly set, protruding 12 ins. above ground.</p>
	<p>Ascend 20 ft. over nearly level land, across open field.</p>
39.90	<p>The center ¼ sec. cor. of sec. 33, established and recorded by Frank Cain, Deputy County Surveyor, in 1909, subsequently perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1949, monumented with an iron pipe, ¾ in. diam., firmly set, protruding 2 ins. above ground, from which the remains of a bearing tree mkd. by Cain:</p>
	<p>A sawed fir stump, 28 ins. diam., bears S. 58¼° E., 63 lks. dist., no marks visible.</p>
	<p>and bearing trees mkd. by Wenderoth</p>
	<p>A fir, 15 ins. diam., bears S. 73¾° W., 201 lks. dist., with healed double blaze.</p>
	<p>A ponderosa pine, 19 ins. diam., bears N. 8½° W., 116 lks. dist., with healed blaze.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>
	<p style="text-align: center;">C ¼ S 33 1972</p>
	<p>from which a new bearing tree</p>
	<p>A fir, 7 ins. diam., bears N. 67½° W., 6 lks. dist., mkd. C¼ S33 BT.</p>