

Subdivision of Section 33, T. 31 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS		
	<p>N. 2° 22' W., beginning new measurement.</p> <p>Ascend slightly over nearly level land.</p>	
19.05	<p>Cow Creek Road, paved, 30 lks. wide, bears N. 10° W. and S. 10° E.</p>	
20.07	<p>From this point, a local corner, established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1949, bears West, 0.012 chs. dist., determined from the remains of bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 15½° E., 109 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A shattered fir stump, size indeterminate, bears S. 52¼° E., 56 lks. dist., no marks visible.</p> <p>Descend 15 ft. over NE. slope.</p>	
25.95	<p>Cow Creek, 30 lks. wide, course S. 20° E.; asc. 25 ft. over SW. slope, across open field.</p>	
40.10	<p>The ¼ sec. cor. of secs. 28 and 33.</p>	
20.13	<p>From the ¼ sec. cor. of secs. 33 and 34.</p> <p>S. 89° 51' W., on the E. and W. center line of sec. 33.</p> <p>Descend 240 ft. over SW. slope, through heavy timber and dense undergrowth.</p> <p>The center E 1/16 sec. cor. of sec. 33, established and recorded by George J. Wenderoth, Deputy County Surveyor, in 1949, monumented with an iron pipe, 1 in. diam., firmly set, protruding 3 ins. above ground, from which bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A white fir, 16 ins. diam., bears N. 69¼° W., 15½ lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A white fir, 25 ins. diam., bears S. 41¾° W., 51½ lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>	
	<p><math display="block">\frac{C \text{ E } 1/16 \text{ C}}{S \text{ 33}}</math> 1972</p>	
	<p>S. 89° 50' W., beginning new measurement.</p> <p>Descend 30 ft. over gentle W. slope.</p>	
1.55	<p>Leave timber and undergrowth; enter open field, edge bears N. and S.</p>	
16.10	<p>Cow Creek, 40 lks. wide, course S. 25° E.; asc. 25 ft. over E. slope.</p>	
17.15	<p>Cow Creek Road, paved, 30 lks. wide, bears N. 30° W. and S. 40° E., in curve.</p>	