

15503

Subdivision of Section 33, T. 31 S., R. 4 W.,
Willamette Meridian, Oregon

<p>CHAINS 40.41</p>	<p>The center S 1/16 sec. cor. of sec. 33.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.</p> <p>N. 3° 30' W., on the N. and S. center line of the SW$\frac{1}{4}$ of sec. 33.</p> <p>Ascend 170 ft. along broken E. slope, through scattered timber and dense undergrowth.</p> <p>14.85 Spur, slopes E.; desc. 80 ft. over NE. slope.</p> <p>18.50 Wet ravine, drains E.; asc. 45 ft. over SE. slope.</p> <p>20.19 Point for the SW 1/16 sec. cor. of sec. 33, at intersection with the E. and W. center line of the SW$\frac{1}{4}$ of sec. 33.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 33 1972</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 70$\frac{1}{2}$° W., 60 lks. dist., mkd. SW 1/16 S33 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 51° W., 23$\frac{1}{2}$ lks. dist., mkd. SW 1/16 S33 BT.</p> <p>Ascend 120 ft. over SE. slope, along the W. edge of a logged area.</p> <p>24.80 Spur, slopes E.; desc. 105 ft. over NE. slope.</p> <p>28.75 Ravine, drains E.; asc. 200 ft. over SE. slope.</p> <p>36.80 Spur, slopes E.; desc. 100 ft. over NE. slope.</p> <p>39.30 Ravine, drains E.; asc. 25 ft. over SE. slope.</p> <p>40.49 The center W 1/16 sec. cor. of sec. 33.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 33.</p> <p>S. 89° 14' W., on the E. and W. center line of the SW$\frac{1}{4}$ of sec. 33.</p> <p>Descend slightly across open field.</p> <p>2.80 Leave open field, enter scattered timber and dense undergrowth, edge bears N. and S.; asc. 360 ft. over SE. slope.</p> <p>20.36 The SW 1/16 sec. cor. of sec. 33.</p> <p>Ascend 230 ft. over SE. slope.</p> <p>29.55 Ravine, drains SE.; asc. 500 ft. over E. slope.</p> <p>40.59 The S 1/16 sec. cor. of secs. 32 and 33.</p>
-------------------------	--