

15505

Subdivision of Section 34, T. 31 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS	
49.50	Foot of mountain, bears E. and W.; desc. 40 ft. over gentle N. slope.
55.85	Cow Creek, 60 lks. wide, course W.; asc. 30 ft. over S. slope.
79.54	The $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
	From the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	S. $89^{\circ} 07' W.$ , on the E. and W. center line of sec. 34.
	Ascend 10 ft. over SE. slope, through scattered timber and dense undergrowth.
1.35	Spur, slopes N. $70^{\circ} E.$ ; desc. 200 ft. along NW. slope.
21.95	Ravine, drains N. $20^{\circ} E.$ ; asc. 195 ft. over NE. slope.
28.40	Spur, slopes N.; desc. 40 ft. along N. slope.
39.75	The center $\frac{1}{4}$ sec. cor. of sec. 34.
	Ascend 5 ft. over NE. slope.
40.75	Spur, slopes N. $20^{\circ} W.$ ; desc. 185 ft. over NW. slope.
45.25	Wet ravine, drains N.; asc. 95 ft. over NE. slope.
49.05	Spur, slopes N.; desc. 45 ft. over NW. slope.
53.70	Wet ravine, drains N. $20^{\circ} E.$ ; asc. 215 ft. over NE. slope.
59.38	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 34.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{W } \frac{1}{16} \text{C} \\ \text{S } 34 \\ 1972 \end{array}$
	from which
	A fir, 15 ins. diam., bears N. $34^{\circ} W.$ , 33 lks. dist., mkd. CW $\frac{1}{16}$ S34 BT.
	A cedar, 36 ins. diam., bears S. $8\frac{1}{2}^{\circ} W.$ , 78 lks. dist., mkd. CW $\frac{1}{16}$ S34 BT.
	Ascend 205 ft. over NE. slope.
66.00	Spur ridge, bears N. and S.; desc. 420 ft. over W. slope.
79.01	The $\frac{1}{4}$ sec. cor. of secs. 33 and 34.
	From the W $\frac{1}{16}$ sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.
	N. $2^{\circ} 03' W.$ , on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 34.
	Ascend 355 ft. over SW. slope, through scattered timber and dense undergrowth.