

15509

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by James Freeman,
U. S. Deputy Surveyor, in 1851,
and the retracement by William Thiel,
U. S. Deputy Surveyor, in 1889)

Beginning at the $\frac{1}{4}$ sec. cor. of sec. 7 only, on the W. bdy. of the Tp., re-established by A. R. Evans, Deputy County Surveyor, in 1951, monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Evans:

A fir stump, 20 ins. diam., bears N. 40° E., 35 lks. dist., no marks visible.

A root hole, bears N. 29° W., 35 lks. dist., with a down fir stump alongside, 14 ins. diam., with scribe marks BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

$\frac{1}{4}$ S 7
T 30 S
R 4 W
1969

from which new bearing trees

A madrone, 9 ins. diam., bears N. $68\frac{1}{2}^\circ$ E., $111\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S7 BT.

A white fir, 9 ins. diam., bears S. $23\frac{3}{4}^\circ$ E., 264 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

N. $0^\circ 26'$ E., along the W. bdy. of sec. 7, marking and blazing the true line.

Ascend 285 ft. over broken SE. slope, through old logged area and moderate undergrowth.

20.70 Enter timber, edge bears NW. and SE.

36.62 The closing cor. of secs. 1 and 12, T. 30 S., R. 5 W., perpetuated and recorded by A. R. Evans, Deputy County Surveyor, in 1951, monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees:

A pine, 33 ins. diam., bears N. $63\frac{1}{2}^\circ$ E., 53 lks. dist., with scribe marks T30S R5W CC visible on partially healed double blaze. (Record, N. $66\frac{1}{2}^\circ$ E.)

A madrone snag, 7 ins. diam., bears S. $29\frac{1}{2}^\circ$ W., 35 lks. dist., with scribe marks 30S R5W S12 BT visible on partially healed double blaze. (Record, S. 22° W.)

and bearing trees mkd. by Evans

A fir, 15 ins. diam., bears S. 41° W., 39 lks. dist., with scribe marks T30S R5W CC S12 CS BT visible on bark blaze.