

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 23 ins. diam., bears N. $58\frac{3}{4}^{\circ}$ W., 42 $\frac{1}{2}$ lks. dist., with scribe marks T30S R5W CC S1 CS BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 30 S	T 30 S
CC $\frac{S 1}{S 12}$	R 4 W
R 5 W	S 7
1969	

Ascend 75 ft. over SE. slope.

39.53

The cor. of secs. 6 and 7 only, perpetuated and recorded by A. R. Evans, Deputy County Surveyor, in 1951, monumented with an iron bar, $\frac{1}{2}$ x 2 ins., firmly set, flush with ground, from which the remains of the original bearing trees:

A root hole, bears N. 69° E., 60 lks. dist., with a down oak stump alongside, 14 ins. diam., with scribe marks T30S R4W S6 visible on open blaze. This tree was rescribed by William Thiel, in 1889.

A root hole, bears S. 46° W., 57 lks. dist., with a down oak stump alongside, 10 ins. diam., no marks visible on decayed blaze.

A madrone, 27 ins. diam., bears N. 3° W., 150 lks. dist., with scribe marks 3 5 1 visible on partially healed blaze. This tree was rescribed by William Thiel, in 1889.

and bearing trees mkd. by Evans

A fir, 25 ins. diam., bears N. $28\frac{1}{2}^{\circ}$ E., 52 lks. dist., with scribe marks T30S R4W S6 CS BT visible on bark blaze.

A fir, 33 ins. diam., bears S. $31\frac{1}{4}^{\circ}$ E., 44 lks. dist., with scribe marks T30S R4W S7 CS BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S	T 30 S
R 5 W	$\frac{S 6}{S 7}$
S 1	R 4 W
1969	

Deposit iron bar alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, oak, cedar, madrone, maple, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, hazel, and reproduction.