

15511

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS									
	N. 0° 41' E., along the W. bdy. of sec. 6.								
	Ascend 15 ft. over SE. slope, through medium timber and moderate undergrowth, along E. edge of timber.								
1.15	Spur, slopes E.; desc. 735 ft. over NE. slope.								
26.30	Packard Gulch, 10 lks. wide, course S. 35° E.; asc. 130 ft. over SW. slope.								
28.40	Gravelled road, 20 lks. wide, bears N. 50° W. and S. 50° E.								
33.05	Ravine, drains SW.; asc. 165 ft. over S. slope.								
36.81	Point for the ¼ sec. cor. of sec. 1 only, T. 30 S., R. 5 W., hereinafter described in the field notes of the dependent resurvey of the subdivisional lines of T. 30 S., R. 5 W.								
	Ascend 60 ft. over SW. slope.								
39.57	The ¼ sec. cor. of sec. 6 only, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees: <p style="margin-left: 40px;">A decayed black oak snag, 12 ins. diam., bears N. 24½° W., 43 lks. dist., with axe marks visible on decayed blaze. (Record, N. 20° W.)</p> <p>and bearing trees mkd. by Markham</p> <p style="margin-left: 40px;">A madrone, 15 ins. diam., bears N. 29° E., 29½ lks. dist., with scribe marks S S6 visible on bark.</p> <p style="margin-left: 40px;">A fir, 37 ins. diam., bears N. 76° W., 17½ lks. dist., with scribe marks BT visible on bark blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <table border="0"> <tr><td> </td><td>T 30 S</td></tr> <tr><td> </td><td>¼ S 6</td></tr> <tr><td> </td><td>R 4 W</td></tr> <tr><td></td><td>1969</td></tr> </table> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A fir, 37 ins. diam., bears N. 83½° E., 32 lks. dist., mkd. ¼ S6 BT.</p> <hr style="width: 20%; margin-left: 40px;"/>		T 30 S		¼ S 6		R 4 W		1969
	T 30 S								
	¼ S 6								
	R 4 W								
	1969								
	N. 0° 34' E., beginning new measurement.								
	Ascend 80 ft. over SW. slope.								
4.80	Spur, slopes S. 30° W.; desc. 50 ft. over NW. slope.								
12.10	Ravine, drains S. 60° W.; asc. 120 ft. over SW. slope.								