

15513

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	From the cor. of Tps. 29 and 30 S., Rs. 4 and 5 W.
	S. 89° 38' W., along the S. bdy. of sec. 36, marking and blazing the true line.
	Ascend 140 ft. over SE. slope, through medium timber and moderate undergrowth.
7.80	Spur, slopes S. 10° W.; desc. 155 ft. over SW. slope.
13.35	Creek, 2 lks. wide, course S.; asc. 400 ft. over E. slope.
24.50	Spur, slopes S. 15° E.; desc. 145 ft. over SW. slope.
30.65	Ravine, drains S.; asc. 155 ft. over SE. slope.
35.30	Spur, slopes S. 10° E.; desc. 35 ft. over SW. slope.
37.90	Ravine, drains S.; asc. 5 ft. over SE. slope.
38.54	Point for the ¼ sec. cor. of sec. 1 only, T. 30 S., R. 5 W., hereinafter described in the field notes of the dependent resurvey of the subdivisional lines of T. 30 S., R. 5 W.
	Ascend 65 ft. over SE. slope.
43.90	Point for the ¼ sec. cor. of sec. 36 only, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.
	Ascend 140 ft. over SE. slope.
51.00	Ridge, bears N. 65° E. and S. 65° W.; desc. 115 ft. over NW. slope.
57.50	Ravine, drains N.; asc. 60 ft. over NE. slope.
62.30	Spur, slopes N. 20° E.; desc. 10 ft. along broken N. slope.
74.00	Gravelled road, 20 lks. wide, bears N. 30° W. and S. 30° E.
76.60	Spur, slopes N. 10° W.; desc. 45 ft. over NW. slope.
77.85	Dirt road, 15 lks. wide, bears NE. and SW.
77.96	Point for the closing cor. of secs. 1 and 2, T. 30 S., R. 5 W., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 S R 5 W S 36 S 2 S 1 C C T 30 S R 5 W 1969
	from which
	A fir, 15 ins. diam., bears S. 32½° E., 83 lks. dist., mkd. T30S R5W S1 CC BT.