

15514

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
83.20	<p>A fir, 12 ins. diam., bears S. $7\frac{1}{4}^{\circ}$ W., 130 lks. dist., mkd. T30S R5W S2 CC BT.</p> <p>Descend 185 ft. over NW. slope.</p> <p>The cor. of secs. 35 and 36 only, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 5 W S 35 S 36 T 30 S R 5 W S 2 1957</p> <p>from which the remains of bearing trees mkd. by Zirpel</p> <p>A root hole, bears N. 46° E., 75 lks. dist., with a down fir alongside, 15 ins. diam., with scribe marks S BT visible on partially healed blaze.</p> <p>A fir, 14 ins. diam., bears N. $87\frac{1}{2}^{\circ}$ W., 42 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963</p> <p>A fir, 15 ins. diam., bears N. 86° E., 44 lks. dist., with scribe marks T29S R5W S36 CS BT visible on partially healed double blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, oak, cedar, madrone, maple, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, vine maple; Oregon grape, blackberry, thimbleberry, hazel, and reproduction.</p>
8.05	<p>S. $89^{\circ} 37'$ W., along the S. bdy. of sec. 35.</p>
9.85	<p>Descend 235 ft. over NW. slope, through medium timber and moderate undergrowth.</p> <p>Ravine, drains S. 55° W.; asc. slightly over SE. slope.</p>
14.28	<p>Spur, slopes S. 50° W.; desc. 115 ft. over SW. slope.</p>
14.32	<p>Wire fence, bears N. 15° E. and S. 15° W.</p>
16.00	<p>Point for the E $1/16$ sec. cor. of sec. 2 only, T. 30 S., R. 5 W., hereinafter described in the field notes of the dependent resurvey of the subdivisional lines, T. 30 S., R. 5 W.</p> <p>Descend 60 ft. over SW. slope, changing to W. slope.</p>
19.62	<p>Ravine, drains N. 80° W.; desc. 35 ft. over NW. slope.</p>
	<p>The E $1/16$ sec. cor. of sec. 35 only, established by James W. Byron, Deputy County Surveyor, in 1969, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 29 S R 5 W E 1/16 S 35 T 30 S R 5 W 1969</p>