

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 5 W., Willamette Meridian, Oregon

15518

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 5 W
S 33 | S 34
T 30 S R 5 W
S 4
1969

from which a new bearing tree

A fir, 13 ins. diam., bears N. 71½° W., 51½ lks. dist., mkd. T29S R5W S33 BT.

Reset iron pipe alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, oak, cedar, madrone, maple, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, hazel, and reproduction.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 30 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the survey by Nathaniel Ford,
U. S. Deputy Surveyor, in 1854,
and the survey and retracement by Oscar F. Thiel,
U. S. Deputy Surveyor, in 1896)

From the cor. of secs. 11, 12, 13, and 14, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1958, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, from which the remains of the original bearing trees:

A fir root crown, bears N. 50° E., 16 lks. dist., with a down decayed fir stump alongside, 16 ins. diam., with scribe marks BT visible on open blaze.

A fir root crown, bears N. 35° W., 20 lks. dist., with a down decayed fir stump alongside, 15 ins. diam., with scribe marks BT visible on open blaze.
(Record, N. 25° W.)

and bearing trees mkd. by Markham

A fir, 11 ins. diam., bears N. 9° E., 32 lks. dist., with healed double blaze.

A fir, 31 ins. diam., bears S. 19° W., 53 lks. dist., with scribe marks S14 BT visible on bark blaze.

A madrone, 5 ins. diam., bears N. 32° W., 17½ lks. dist., with healed double blaze.

A fir, 13 ins. diam., bears N. 19° W., 37½ lks. dist., with healed double blaze.

At the corner point