

15519

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.						
	<p>T 30 S R 5 W</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">S 11</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 12</td> </tr> <tr> <td style="padding: 0 5px;">S 14</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 13</td> </tr> </table> <p>1969</p>	S 11		S 12	S 14		S 13
S 11		S 12					
S 14		S 13					
	<p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 77½° E., 29½ lks. dist., mkd. T30S R5W S13 BT.</p> <p>N. 0° 04' W., bet. secs. 11 and 12, marking and blazing the true line.</p> <p>Descend 295 ft. over N. slope, through medium timber and moderate undergrowth.</p>						
6.00	Slope changes to NE., also enter logged area, edge bears E. and W.						
13.70	Morgan Creek, 8 lks. wide, course S. 55° E.; asc. 165 ft. over SW. slope.						
18.00	Morgan Creek Road, gravelled, 10 lks. wide, bears NW. and SE., curving S.						
23.30	Spur, slopes S. 80° W.; desc. 30 ft. over NW. slope.						
25.60	Creek, 2 lks. wide, course S. 75° W.; asc. 145 ft. over S. slope.						
30.70	Spur, slopes S. 55° W.; asc. 60 ft. over W. slope.						
37.50	Slope changes to SW.						
39.24	<p>The ¼ sec. cor. of secs. 11 and 12, perpetuated and recorded by A. R. Evans, Deputy County Surveyor, in 1951, monumented with an iron pipe, ½ in. diam., firmly set, flush with the ground, and subsequently perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, with an iron rod, ¾ in. diam., firmly set alongside, projecting 10 ins. above ground, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A root hole, bears S. 43¼° E., 8 lks. dist., with a down and burned fir alongside, 25 ins. diam., no marks visible.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears S. 65½° E., 83½ lks. dist., with scribe marks ¼ S12 CS BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A burned fir snag, 10 ins. diam., bears S. 76° W., 32½ lks. dist., with scribe marks ¼ S11 CS BT visible on opened double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p>						