

15520

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS		
	T 30 S R 5 W $\frac{1}{4}$ S 11 S 12 1969	
	from which a new bearing tree A madrone, 21 ins. diam., bears N. $15\frac{3}{4}^{\circ}$ W., 124 lks. dist., mkd. $\frac{1}{4}$ S11 BT. Deposit iron rod alongside iron post.	
	<hr/> N. $0^{\circ} 05'$ W., beginning new measurement.	
	Ascend 50 ft. over SW. slope, through old burn with medium timber and moderate undergrowth.	
2.60	Spur, slopes S. 75° W.; desc. 175 ft. over NW. slope.	
5.10	Wire fence, bears N. 70° E. and S. 70° W.	
10.00	Bottom of descent, slopes S. 75° W., also enter meadow, edge bears N. 75° E. and S. 75° W.; asc. 370 ft. over S. slope.	
16.15	Wire fence, bears E. and W., also enter old burn with medium timber and moderate undergrowth, edge bears same as fence.	
25.70	Spur, slopes S. 55° W.; desc. 225 ft. over NW. slope.	
38.45	The cor. of secs. 1, 2, 11, and 12, perpetuated and re- corded by John H. Markham, Jr., Registered Engineer No. 2880, in 1958, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees: A maple, 17 ins. diam., bears N. 72° E., 55 lks. dist., with healed blaze. A burned fir root crown, 26 ins. diam., bears S. 33° E., 24 lks. dist., no marks visible. A burned fir stump, 38 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ W., 23 lks. dist., no marks visible. (Record, 33 lks.) and the remains of bearing trees mkd. by Markham A cedar snag, 8 ins. diam., bears S. 85° E., 38 lks. dist., with healed double blaze. A maple, 10 ins. diam., bears N. 6° W., $47\frac{1}{2}$ lks. dist., with scribe marks S2 BT visible on partially healed double blaze. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.	
	T 30 S R 5 W S 2 S 1 S 11 S 12 1969	